


LED recessed downlight, DALI dimmable
Artikel-Nr. 41553074



LED recessed downlight, DALI dimmable, round. In a compact design, for installation in tool-less rapid assembly systems
Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 30W, Amount of light sources / fittings: 1.0 Qty, Light colour : White, Beam angle: 40°, Adjustability: Not adjustable, With control gear: Yes, control: DALI.

Artikel-Nr.	41553074
Stand:	06.09.2021 13:35

Colour temperature	4000 K
Beam angle	40 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass / Plastic
Lamp	LED
Shipping	Incl. converter for connection to 230 V mains voltage, DALI-2 dimmable and connection box
Colour rendering	CRI > 80
Glare evaluation	UGR < 19

Control	DALI
Outer diameter	175 mm
Built-in diameter	150 mm
Installation depth	85 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Not adjustable
Circuit type	Parallel conduction
Suitable for through-wiring	Yes