


LED surface mounted reading light ARCUS
Artikel-Nr. 10190073



LED surface mounted reading light ARCUS, round. Surface mounting, Wall-mounted. Including an integrated on/off switchable switch, dimensions mounting housing: diameter 76 mm, height 29 mm, flexible arm length: 250 mm, cylinder diameter: 30 mm. Mounting method: Surface mounting, Place of installation: Wall-mounted, Material: Aluminium / Steel, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 4.2W, Luminous flux: 290lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 41 °, With control gear: Yes, Control: on/off.

Artikel-Nr.	10190073
Stand:	07.12.2021 11:04
Colour temperature	3000 K
Luminous flux	290 lm
Beam angle	41 °
Material	Aluminium / Steel
Power	4,2 W
Lamp	LED
scope of delivery	Incl. converter for connection to the 230-V mains voltage
Colour rendering	CRI > 80
Control	on/off
Voltage	230V AC 50Hz
Circuit type	Parallel conduction
Degree of protection	IP20
Protection class	I
Aufbauhöhe	29 mm
Outer diameter	76 mm