




PANAY MIDI LED surface-mounted ceiling light, switchable, with microwave motion sensor

Article no. 12577073

Light.
For Generations.**Tender**

LED surface-mounted ceiling light, switchable, with microwave motion sensor, Round. Luminaire diameter 350.0 mm, Height 62.0 mm Weight 0.38 kg, with rotationssymmetrical, deep, wide distributed light intensity. optimal light distribution due to a plastic, opal cover. Luminous flux 1.130 lm, Power 1 x 19 W, Light colour warm white, Correlated color temprature (CCT) 3.000 K, Colour rendering index CRI > 80, Rated life time L70/B50 at 25 °C: 50.000 h, Housing material: Steel / Plastic, Colour: White, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP20, shock resistance according to IEC62262: IK05. With electronic driver, on/off switchable.

Product Benefits

- Attractively priced surface-mounted ceiling or wall light in round design.
- Version 3,000 K, switchable, with microwave sensor.
- Three different sizes available.
- Also available in 3CCT version (3,000 K / 4,000 K / 6,000 K) and phase cut-off dimmable available.

PANAY MIDI LED surface-mounted ceiling light, switchable, with microwave motion sensor

Article no. 12577073

Light.
For Generations.

Article data	
Article no.	12577073
GTIN	4255752500667
Series name	PANAY MIDI
Short description	LED surface-mounted ceiling light, switchable, with microwave motion sensor
Material	Steel / Plastic
Colour	White
Type of surface	Glossy
Shape	Round
Outer diameter	350 mm
Hight	62 mm
Scope of delivery	incl. converter for connection to 230 V mains voltage, switchable and microwave motion sensor
Weight	0.380 kg
Conformance	UKCA

Lighting technology	
Colour temperature	3.000 K
Light colour	White
Light output	Direct
Luminous flux	1,130 lm
System efficiency	59 lm/W
Colour rendering	CRI > 80
Beam angle	120°
Light sharing	Symmetric
Adjustable color temperature	No

Operating technology of the luminaire	
System output	19 W
Voltage type	AC
AC nominal voltage max	230 V
Frequency max	50 Hz
Lamp	LED
Protection class	I
Degree of protection	IP20
Dimmable	No
Control	on/off
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Rated life time L70/B50 at 25 °C	50,000 h

Mounting technology	
Mounting method	Surface mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Impact resistance	IK05
Material cover	Plastic, opal

Packing data	
Gross weight	0.42 kg
Length of packaging	360 mm
Packaging width	360 mm
Packaging hight	70 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

PANAY MIDI LED surface-mounted ceiling light, switchable, with microwave motion sensor

Article no. 12577073

Light.
For Generations.