LED Arbeitsplatzleuchte
LED workplace luminaire

UNILED II TUNABLE WHITE Gelenkarm, 3000~6500K, dimmbar, Leuchtenbreite 548 mm

Artikelnr.:	120700-02
EAN:	4260556623184

Bestell-Nr.:	120710-01
Modell:	UNILED II
Bauform:	LED Gelenkarmleuchte
Leuchtmittel:	SUNlike LED
Lampenleistung:	~28 W
Lampenlichtstrom:	2373 lm (6500 K) / 2202 lm (2700 K)
Lampenlichtausbeute:	ca. 96 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Warmweiß (2700 K) bis Tageslichtweiß (6500 K)
Anschlusswert Leuchte:	24V DC ± 10%
Betriebsgerät:	Netzteil 100-240V AC inkl.
Anschluss Leuchte:	M12 A-kodiert
Anschlusswert Netzteil::	110-240V AC
Anschluss Netzteil:	EURO Stecker zu M12 Steckverbinder
Schutzart:	IP40
Schutzklasse:	III
Entblendung:	opalweiß
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +40 °C
Farbwiedergabe (Ra):	> 90/98
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium / Kunststoff
Material Abdeckung:	Makrolon
Länge Kopf [A]:	548 mm
Länge Gelenkarme:	2x 400 mm
Gewicht:	2250 g
Bruttogewicht:	3950 g
Risikogruppe:	freie Gruppe
Befestigungszubehör:	Tischklemme inkl.
Dimmbar:	Dimmer mit Memory Funktion intern
Gefertigt in:	Deutschland
Besonderheit:	TUNABLE WHITE: sehr hohe Farbwiedergabe, stufenlos einstellbare Lichtfarbe von 3000 K bis 6500 K



Lampenlebensdauer in Betriebstunden (L80/B10)

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com | Shop.led2work.com

LED Arbeitsplatzleuchte
LED workplace luminaire

UNILED II TUNABLE WHITE Gelenkarm (adjustable arm), 3000~6500K, dimmable, luminaire head width 548 mm

Item number:	120700-02
EAN:	4260556623184

Order number:	120710-01
Model:	UNILED II
Type:	LED adjustable arm luminiare
Illuminant:	SUNlike LED
Power consumption:	~28 W
Lamp luminous flux:	2373 lm (6500 K) / 2202 lm (2700 K)
Lamp luminous efficiency:	ca. 96 lm/W
Light distribution:	direct
Light colour:	warm white (2700 K) up to daylight white (6500 K)
Connected load:	24V DC ± 10%
Power supply:	included external PSU 100-240V AC
Connection (connector):	M12 A-type encoded
Connected load PSU:	110-240V AC
Connection PSU:	EURO plug to connector M12
Degree of protection:	IP40
Class of protection:	III
Glare-free	opal white
Beam angle (optics):	100°
Operating temperature:	-10... +40 °C
Colour rendering (Ra):	> 90/98
Lamps lifetime:	> 60,000 h
Housing material:	aluminium / plastics
Cover material:	Makrolon®
Head width [A]:	548 mm
Length adjustable arms:	2x 400 mm
Weight (net):	2250 g
Gross weight:	3950 g
Risk group (DIN EN 62471):	free group
Mounting accessories:	included table clamp
Dimmable:	internal dimmer with memory function
Made in:	Germany
Feature:	TUNABLE WHITE: very high colour rendering, continuously adjustable light colour from 3000 K up to 6500 K



Lamps lifetime in operation hours (L80/B10)

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com | Shop.led2work.com