BRUMBERG

# Recessed spot, GX5,3

**Artikel-Nr. 2169.02**






Recessed spot, GX5,3, chrome, round. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: GX5.3, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V, Power: 50W, Amount of light sources / fittings: 1.0 Qty, Adjustability: Pivoted, With control gear: No, control: Dimming depending on driver.

| | |
|---|---|
| **Artikel-Nr.** | **2169.02** |
| **Stand:** | 20.07.2021 22:39 |

| | |
|---|---|
| Colour | Chrome |
| Amount of light sources / fittings | 1 Qty |
| control | Dimming depending on driver |
| Outer diameter | 82 mm |
| Brackets | 5366 |
| Built-in diameter | 68 mm |
| Installation depth | 55 mm |
| Material | Aluminium |
| Height | 2 mm |
| Lamp holder | GX5.3 |

| | |
|---|---|
| Power | max. 50 W |
| Voltage | 12V |
| Lamp | for LED-retrofill lamp |
| Circuit type | Parallel conduction |
| Degree of protection | IP20 |
| Protection class | III |
| Swivel angle | 25 ° |
| Voltage type | AC/DC |
| Adjustability | Pivoted |

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.