


LED pendant profile luminaire BIRO60, with microprismatic cover

Artikel-Nr. 77201693



LED pendant profile luminaire BIRO60, with microprismatic cover, silver, rectangular. Surface mounting, Ceiling-mounted. Optical unit: Microprisms. Pendant length: maximum 1,500 mm, weight: 2.5 kg. Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 27W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 2.500lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 80°, With control gear: Yes, control: on/off.

Artikel-Nr.	77201693
Stand:	22.07.2021 01:43

Colour of light	3000 K
Colour	Silver
Length	1155 mm
Beam angle	80 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Steel / Plastic
Power	27 W
Lamp	LED
Colour rendering	CRI > 80
Glare evaluation	UGR < 19
control	on/off

Voltage	230V AC 50Hz
Luminous flux	3,386 lm
Degree of protection	IP20
Protection class	I
Length	1155 mm
Width	60 mm
Height	78 mm
Circuit type	Parallel conduction
Pendulum length max.	1,500 mm
Pendulum length min.	150 mm
Suitable for through-wiring	No