BRUMBERG

LED recessed spot

Artikel-Nr. 12281153





LED recessed spot, nickel, round. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 700 mA, Power: 26W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 2.250lm, Colour temperature: 2700 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: No, control: Dimming depending on driver.

Artikel-Nr.	**12281153**
Stand:	21.07.2021 02:20

Colour of light	2700 K
Colour	Nickel
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass
Lamp holder	Plug&Play
Power	26 W
Lamp	LED
Colour rendering	CRI > 80
control	Dimming depending on driver

Outer diameter	160 mm
Built-in diameter	140 mm
Installation depth	90 mm
Current	700 mA
Luminous flux	2,250 lm
Degree of protection	IP20
Protection class	III
Adjustability	Pivoted
Swivel angle	25 °
Circuit type	Series conduction

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.