


Ceiling recessed speaker, DA 180 mm  
**Artikel-Nr. 3094.07**



Ceiling recessed speaker, DA 180 mm, white, round. In a compact design, for installation in tool-less rapid assembly systems. Nominal / music load capacity: 40 / 50 W, impedance: 8 Ohm, Sound pressure level: 1 W / 1 m: 90 dB (at nominal output of 98 dB), Transmission range (-3 db): 100 - 20,000 Hz, Transmission range (-10 db): 60 - 23,000 Hz, Model: Front and mounting ring made of plastic with perforated plate cover in white, Net weight: 1.0 kgInstallation in ceilings with material thickness of 1-20 mm. Connection using 2-core cable with connecting terminals. Moisture-impregnated membrane: Restricted protection against moisture (not suitable forcontinuous operation in outdoor area). Mounting method: Recessed mounting, Place of instal-lation: Ceiling-mounted, Material: Steel / Plastic, Degree of protection: according to DIN EN 60529 IP20, Power: 50W.

|             |                  |
|-------------|------------------|
| Artikel-Nr. | 3094.07          |
| Stand:      | 06.12.2021 10:47 |

|                   |                 |
|-------------------|-----------------|
| Colour            | White           |
| Material          | Steel / Plastic |
| Outer diameter    | 196 mm          |
| Built-in diameter | 180 mm          |

|                      |        |
|----------------------|--------|
| Installation depth   | 75 mm  |
| Degree of protection | IP20   |
| Width                | 196 mm |