




**BB09 LED recessed spot set, trailing-edge phase dimmable**  
Article no. 39369223

Light.  
For Generations.



**Tender**  
LED recessed spot set, trailing-edge phase dimmable, Round. Toolless ceiling installation by installation springs. Ceiling cut-out Ø 68 mm, Installation depth 38 mm, Outer diameter 82 mm, Weight 0,157 kg, Reflector silver with rotationssymmetrical, deep, wide distributed light intensity. Cover plastic, transparent. Luminous flux 640 lm, Power 1 x 6 W, Light colour warm white, Correlated color temperature (CCT) 3.000 K, Colour rendering index CRI > 80, Housing material: Stainless steel / Aluminium / Plastic, Colour: Stainless steel, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP20. With electronic driver, Trailing-edge phase dimmable.

| Article data       |                                                     |
|--------------------|-----------------------------------------------------|
| Article no.        | 39369223                                            |
| GTIN               | 4251433917007                                       |
| Series name        | BB09                                                |
| Short description  | LED recessed spot set, trailing-edge phase dimmable |
| Material           | Stainless steel / Aluminium / Plastic               |
| Colour             | Stainless steel                                     |
| Type of surface    | Matt                                                |
| Shape              | Round                                               |
| Outer diameter     | 82 mm                                               |
| Built-in diameter  | 68 mm                                               |
| Installation depth | 38 mm                                               |
| Height             | 3 mm                                                |
| Weight             | 0.157 kg                                            |
| Conformance        | CE, UKCA                                            |

**BB09 LED recessed spot set, trailing-edge phase dimmable**

Article no. 39369223

Light.  
For Generations.

| Lighting technology          |            |
|------------------------------|------------|
| Colour temperature           | 3.000 K    |
| Light colour                 | White      |
| Light output                 | Direct     |
| Luminous flux                | 640 lm     |
| System efficiency            | 107 lm/W   |
| Colour rendering             | CRI > 80   |
| Reflector                    | High-gloss |
| Reflector colour             | silver     |
| Beam angle                   | 38°        |
| Light sharing                | Symmetric  |
| Adjustable color temperature | No         |

| Operating technology of the luminaire |                    |
|---------------------------------------|--------------------|
| Power                                 | 6 W                |
| Current                               | 350 mA             |
| Lamp                                  | LED not changeable |
| Protection class                      | III                |

| Operating technology of driver |                     |
|--------------------------------|---------------------|
| Article No. of used driver     | 17663010            |
| Length                         | 110 mm              |
| Width                          | 50 mm               |
| Hight                          | 19 mm               |
| AC nominal voltage min         | 198 V               |
| AC nominal voltage max         | 264 V               |
| Frequency max                  | 60 Hz               |
| Dimmable                       | Yes                 |
| Control                        | Trailing-edge phase |
| Starting current               | 1A (15,2 µs)        |
| Power min                      | 2.8 W               |
| Power                          | 7 W                 |
| Output current                 | 350 mA              |
| Degree of protection           | IP20                |
| Protection class               | II                  |
| Flicker-free                   | Yes                 |

| Mounting technology         |                                           |
|-----------------------------|-------------------------------------------|
| Mounting method             | Recessed mounting                         |
| Place of installation       | Ceiling-mounted                           |
| Adjustability               | Pivoted                                   |
| Swivel angle                | 25°                                       |
| Max. ceiling thickness      | 13 mm                                     |
| Further references          | No cover with thermal insulation material |
| Material cover              | Plastic, transparent                      |
| Suitable for through-wiring | Yes, with optional accessories            |

| Packing data            |                                                                                                                                                                                                                                                                                                                                                                                |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Gross weight            | 0.189 kg                                                                                                                                                                                                                                                                                                                                                                       |
| Length of packaging     | 95 mm                                                                                                                                                                                                                                                                                                                                                                          |
| Packaging width         | 75 mm                                                                                                                                                                                                                                                                                                                                                                          |
| Packaging hight         | 95 mm                                                                                                                                                                                                                                                                                                                                                                          |
| Disposal at end of life | <p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p> |