

INSTRUCTION

Arelo
901704.002.76



RZB
LIGHTING



≈ 220 - 240 V 0/50/60 Hz IP 20, IP 44 IK05



4 x 1,5 mm²



1,50 mm²



[mm]



[mm]



LED



1 x 20,3 W

D 225, H 4

DA 200, HE 140,
HEL 98, S 1-25



2700



23



A++



A++



718 g

CCT [K]

4000

CRI

80

RG

RG 1




20 A / 50 μs



50



80



INSTRUCTION
WARTUNGSPLAN/
MAINTENANCE
SCHEDULE

DIN EN 61340-5-1



EN 12464
EN 13201




EN 12464
EN 13201



<100%









EN 12464








2019-12-12

www.rzb.de

1








D	H	DA	LE	BE	HE	HEL	S
130	2	105	350	350	100	71	1 - 25
172	2	150	450	450	140	92	1 - 25
225	4	200	500	500	140	98	1 - 25



Der Abstand zu beleuchteten Gegenständen muss min. 0,1 m betragen! /
 The distance to the direct illuminated objects must be at least 0,1 m!



Nicht zur Abdeckung mit
 Wärmedämm-Material
 geeignete Leuchten. /
 Not to be covered with
 thermal insulation material.



Bei Fragen zu unseren Symbolen, besuchen sie folgende Webseite:
 If you have any questions about our signs, visit the following website:

www.rzb.de/fileadmin/assets/downloads/PDF/RZB_Symbolklaerung.pdf





ToLEDo / Arelo	CCT	Φ  [lm]
901699.002.76	3000K / 4000K	700lm / 750lm
901700.002.76	3000K / 4000K	1650lm / 1800lm
901701.002.76	3000K / 4000K	2500lm / 2700lm
901702.002.76	3000K / 4000K	700lm / 750lm
901703.002.76	3000K / 4000K	1650lm / 1800lm
901704.002.76	3000K / 4000K	2500lm / 2700lm

IP20




IP44

oberhalb der Decke IP20
above ceiling IP20

unterhalb der Decke IP44
below the ceiling IP44







RZB - Rudolf Zimmermann, Bamberg GmbH

Rheinstraße 16
96052 Bamberg

Telefon: 0951/7909-0
Telefax: 0951/7909-198

E-mail: info@rzb-leuchten.de