
BRUMBERG

LED recessed downlight, TunableWhite

Artikel-Nr. 12424074





LED recessed downlight, TunableWhite, white, round. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 24V, Power: 11W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 730lm, Colour temperature: from 2.700 K up to 6.000 K, Beam angle: 100°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	**12424074**
Stand:	25.10.2021 22:15

Colour temperature	2700 K - 6000 K
Colour	White
Beam angle	120 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Power	11* W
Lamp	LED
Colour rendering	CRI > 80
Control	Dimming depending on driver

Outer diameter	146 mm
Built-in diameter	130 mm
Installation depth	55 mm
Voltage	24V
Degree of protection	IP20
Protection class	III
Adjustability	Not adjustable
Circuit type	Parallel conduction

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.