


BRUMBERG

LED recessed downlight
Artikel-Nr. 12553179









LED recessed downlight, white, round. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic / Steel, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 32.5W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 2.720lm, Light colour : White, Beam angle: 70°, Adjustability: Not adjustable, With control gear: Yes.

Artikel-Nr.	**12553179**
Stand:	20.07.2021 12:18

Colour	White
Beam angle	70 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic / Steel
Power	32,5 W
Lamp	LED
Colour rendering	CRI > 90
Glare evaluation	UGR < 22

Outer diameter	230 mm
Built-in diameter	210 mm
Installation depth	95 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Not adjustable
Circuit type	Parallel conduction

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.