BRUMBERG

Recessed spot, GX5,3

Artikel-Nr. 1925.07





Recessed spot, GX5,3, white, round. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: GX5.3, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Steel, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V, Power: 50W, Amount of light sources / fittings: 1.0 Qty, Adjustability: Pivoted, With control gear: No, control: Dimming depending on driver.

Artikel-Nr.	**1925.07**
Stand:	19.07.2021 23:06

Colour	White
Amount of light sources / fittings	1 Qty
control	Dimming depending on driver
Outer diameter	80 mm
Brackets	5364
Built-in diameter	68 mm
Installation depth	50 mm
Material	Steel
Lamp holder	GX5.3
Power	max. 50 W

Voltage	12V
Lamp	for LED-retrofill lamp
Circuit type	Parallel conduction
Degree of protection	IP20
Protection class	III
Swivel angle	25 °
Voltage type	AC/DC
Circlip	Without circlip
Adjustability	Pivoted

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.