LED Arbeitsplatzleuchte
LED workplace luminaire

UNILED II Gelenkarm Watchmaker, 5200-5700K, Leuchtenbreite 380 mm

Artikelnr.:	120910-01
EAN:	4260556624785

Bestell-Nr.:	120910-01
Modell:	UNILED II Gelenkarm
Bauform:	LED Gelenkarmleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~19 W
Lampenlichtstrom:	2139 lm
Lampenlichtausbeute:	131 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24V DC ± 10%
Betriebsgerät:	Netzteil 100-240V AC inkl.
Anschluss Leuchte:	M12 A-kodiert
Anschlusswert Netzteil::	110-240V AC
Anschluss Netzteil:	EURO Stecker zu M12 Steckverbinder
Schutzart:	IP40
Schutzklasse:	III
Entblendung:	opalweiß
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +60 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium / Kunststoff
Material Abdeckung:	Makrolon
Länge Kopf [A]:	380 mm
Länge Gelenkarme:	1x 400 mm, 1x 250 mm
Gewicht:	ca. 1900 g
Bruttogewicht:	3550 g
Risikogruppe:	freie Gruppe
Befestigungszubehör:	Tischklemme inkl.
Dimmbar:	optional über Zubehör
Gefertigt in:	Deutschland
Besonderheit:	Mittlere Leuchtenkopfbreite und verkürzter Vorderarm



Lampenlebensdauer in Betriebstunden (L80/B10)

2021_V2_LED2WORK_Datenblatt Arbeitsplatzleuchte Doppelarme 14. 4. 2022, 11:28

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com | Shop.led2work.com

UNILED II Gelenkarm (adjustable arm) Watchmaker, 5200-5700K, luminaire head width 380 mm

Item number:	120910-01
EAN:	4260556624785

Order number:	120910-01
Model:	UNILED II Gelenkarm (adjustable arm)
Type:	LED adjustable arm luminiare
Illuminant:	SMD LED
Power consumption:	~19 W
Lamp luminous flux:	2139 lm
Lamp luminous efficiency:	131 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC ± 10%
Power supply:	included external PSU 100-240V AC
Connection (connector):	M12 A-type encoded
Connected load PSU:	110-240V AC
Connection PSU:	EURO plug to connector M12
Degree of protection:	IP40
Class of protection:	III
Glare-free	opal white
Beam angle (optics):	100°
Operating temperature:	-10... +60 °C
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60,000 h
Housing material:	aluminium / plastics
Cover material:	Makrolon®
Head width [A]:	380 mm
Length adjustable arms:	1x 400 mm, 1x 250 mm
Weight (net):	ca. 1900 g
Gross weight:	3550 g
Risk group (DIN EN 62471):	free group
Mounting accessories:	included table clamp
Dimmable:	via optional accessory
Made in:	Germany
Feature:	mid-level luminaire head width and shortened forearm



Lamps lifetime in operation hours (L80/B10)

2021_02_LED2WORK_Datenblatt Arbeitsplatzleuchte Dokumente 14. 4. 2022, 11:28

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com | Shop.led2work.com