

INSTRUCTION

LINEDO

951263.940.400.200



RZB
LIGHTING


≈ 220 - 240 V 0/50/60 Hz IP 20




CE ENEC



5 x 2,5 mm²



Umgebungstemperatur /
temperature ambiante
=> -25 °C ... + 50 °C



L 1163, B 88, H 235



LED



4 kg

Φ [lm]

5700

P [W]

58

P

2 x 26 W

CCT [K]

4000

CRI

95

RG

RG 1

EEK

A+

EEK

A+



9 A / 65 µs



10



17



17



28

P_f

0,88



T20




INSTRUCTION
WARTUNGSPLAN/
MAINTENANCE
SCHEDULE



DIN EN 61340-5-1



EN 12464
EN 13201



EN 12464
EN 13201



<100%









100%





EN 12464
















7






8





9



10




11








12




13







14




15



Werkseinstellung L1 /
Factory setting L1




16







17




18



19



20







21













22



23



24







Bei Fragen zu unseren Symbolen,
besuchen Sie folgende Webseite:



If you have any questions about our
signs, visit the following website:

www.rzb.de/fileadmin/assets/downloads/PDF/RZB_Symbolklaerung.pdf





	982678.000	Einspeisung Feed	L 312, B 58, H 76	600 g
	982678.000.1	Einspeisung Feed	L 330, B 58, H 76	728 g
	982698.000	Einspeisung Feed	L 330, B 58, H 76	850 g
	982698.000.1	Einspeisung Feed	L 312, B 58, H 76	850 g
	982698.000.2	Einspeisung Feed	L 349, B 58, H 76	850 g
	982661.000	Pendelset Pendant kit	, LP 1500	56 g
	982662.000	Pendelset Pendant kit	, LP 1500	240 g
	982663.000	Befestigungsset Fixture	L 33, B 54,	63 g
	982664.000	Befestigungsset Fixture	L 33, B 54,	39,1 g
	982665.000	Pendelset Pendant kit	, LP 1500	80 g
	982717.000	Pendelset Pendant kit	, LP 5000	190 g
	982718.000	Pendelset Pendant kit	, LP 5000	800 g



	982719.000	Pendelset Pendant kit	, LP 5000	270 g
	982580.010	Deckenmontageset Ceiling surface mounting kit	L 70, B 28, H 16	44 g
	982666.000	Befestigungsset Fixture	L 70, B 54, H 22	25 g
	982699.009	Endkappe End cap	L 16, B 58, H 76	21,5 g
	982700.009	Endkappe End cap	L 23, B 58, H 76	31 g
	982680.000	Verbinder Connector	L 300, B 48, H 9	181 g
	982370.000		D 74, H 3	33 g
	982370.010		D 74, H 3	33 g
	982371.003		D 74, H 3	1,7 g
	982369.003		D 82, H 55	84 g
	982369.013		D 82, H 55	84 g
	982369.023		D 82, H 55	84 g



	982421.002	D 82, H 31	28 g
	982368.003	D 82, H 55	25 g
	982368.013	D 82, H 55	25 g
	982368.023	D 82, H 55	25 g
	982369.033	D 82, H 55	89 g
	982369.043	D 82, H 55	89 g
	982419.002	D 82, H 20	13 g
	982368.033	D 82, H 55	25 g
	982647.002	D 87, H 41	200 g
	982648.002	D 87, H 76	240 g



RZB - Rudolf Zimmermann, Bamberg GmbH

Rheinstraße 16
96052 Bamberg

Telefon: 0951/7909-0
Telefax: 0951/7909-198

E-mail: info@rzb-leuchten.de