




LED Arbeitsplatzleuchte

LED workplace luminaire






UNILED SL, 545 mm, 24V DC, Abdeckung Mikroprismen

Artikel-Nr.:	110914-22
EAN:	4260556623399

Bestell-Nr.:	110914-22
Modell:	UNILED SL
Bauform:	LED System- und Arbeitsplatzleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~24 W
Lampenlichtstrom:	3217 lm
Lampenlichtausbeute:	131 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24V DC $\pm$ 10%
Anschluss Leuchte:	M12 A-kodiert
Schutzart:	IP50
Schutzklasse:	III
Entblendung:	Mikroprismen
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +60 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Kunststoff Mikroprismen
Höhe [B] x Breite [C]:	35 mm x 85 mm
Länge [A]:	545 mm / 575 mm
Gewicht:	850 g
Bruttogewicht:	1300 g
Risikogruppe:	freie Gruppe
Befestigungszubehör:	optional
Dimmbar:	optional über Zubehör
Kennzeichnung:	CE, ETL Listed
Gefertigt in:	Deutschland
Besonderheit:	Hohe Lichtstreuung

Lampenlebensdauer in Betriebstunden (L80/B10)

LED Arbeitsplatzleuchte LED workplace luminaire



UNILED SL, 545 mm, 24V DC, micro prisms cover

Item number:	110914-22
EAN:	4260556623399

Order number:	110914-22
Model:	UNILED SL
Type:	LED system luminaire and workplace lighting
Illuminant:	SMD LED
Power consumption:	~24 W
Lamp luminous flux:	3217 lm
Lamp luminous efficiency:	131 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC $\pm$ 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP50
Class of protection:	III
Glare-free	micro prisms
Beam angle (optics):	100°
Operating temperature:	-10... +60 °C
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60,000 h
Housing material:	aluminium
Cover material:	micro prisms cover
Height [B] x Width [C]:	35 mm x 85 mm
Length [A]:	545 mm / 575 mm
Weight (net):	850 g
Gross weight:	1300 g
Risk group (DIN EN 62471):	free group
Mounting accessories:	optional
Dimmable:	via optional accessory
Marking:	CE, ETL Listed
Made in:	Germany
Feature:	high light diffusion

Lamps lifetime in operation hours (L80/B10)