


Product features and key data

Luminaire type	Multi-variable and modern tube luminaire with 75 mm profile diameter.
Mounting method	Surface-mounting Suspension
Luminaire optic	Cylindrical profile with photometrically effective prismatic structure as secondary optic.
Connected load	36 W
Power factor	0,95
Colour temperature	4.000 K
Rated luminous flux	6.400 lm
Luminous efficacy	177 lm/W
Interchangeability lightsource	Yes - interchangeable
Service life	L80 (25 °C) = 100.000 h
Colour rendering index	80
Colour tolerance	3 SDCM
Photobiological class	Group 0 - no risk
Luminaire colour	RAL7035 Light grey
Luminaire body	Luminaire profile made of polycarbonate (PC).
Electrical version	With electronic transformer, digitally dimmable (DALI).
DALI-2-Standard EN 62386	Yes
Connection method	Plug-in terminal
Touch-Dim-capable	Yes
Dimming range	1 - 100 %
Mains frequency	0/50/60 Hz
Mains voltage	220 - 240 V
Ingress Protection (IP) rating	IP66
Protection rating on room side	IP66
Protection class	I
Impact resistance (IK)	IK10
Hot wire resistance	850 °C
Ambient temperature	-40 - 45 °C
Max. Luminaires B10	21
Max. Luminaires B16	36
Max. Luminaires C10	37
Max. Luminaires C16	60
Net length	1.849 mm
Net width	75 mm
Net height	75 mm
Outside diameter	75 mm
Weight	3,8 kg

light distribution curve

**TugraHE+ 18 PN 64-840 ETDD PC 23
TX302915**

UGR I = 19,6
UGR q = 17,8
DIN 5040: B50
UTE: 0,89 C + 0,11 T
CEN Flux Code: 66 87 95 89 100 13 30 61 11

■ C0 - C180
■ C90 - C270

Available accessories

Material	Description
Tugra ZLV/315/18 8117200	Through-wiring, 3-core. For luminaires from seriesTugra 18...
Tugra ZLV/515/18 8117300	Through-wiring, 5-core. For luminaires from seriesTugra 18...
Tugra ZLV/715/18 8117400	Through-wiring, 7-core. For luminaires from seriesTugra 18...
Tugra ZSDT/2000 8117800	Wire suspension for luminaires of series Tugra. With loop for ceiling suspension. With metal clamp for use of triangle.
Tugra ZSDD/2000 8117900	Wire suspension for luminaires of series Tugra. With decorative ceiling connection. With threaded sleeve for attachment to mounting clip.
Tugra ZSSD/2000 8118000	Wire suspension for luminaires of series Tugra. With loop for ceiling suspension. With threaded sleeve for attachment to mounting clip.
Tugra ZBRS 8118100	Tube clip for wall and ceiling mounting and also suitable for suspended mounting by means of separate accessories. Packaging unit has 1 piece.
Tugra ZBWM 8118200	Pivotable mounting brackets for wall mounting. Packaging unit 2 pieces.
Tugra ZB V2A 8118300	Standard stainless steel mounting clips (2 pieces, V2A) for wall and ceiling fixing with triangle for holding components for suspended mounting.
Tugra ZB V4A 8118400	Stainless steel mounting clips (2 pieces, V4A) for wall and ceiling fixing with triangle for holding components for suspended mounting. Design is particularly suitable for use in environments with chlorine and saline atmospheres.
Tugra ZBATL 8118500	Disassembly protection for horizontal wall mounting. 1 set= 2 pieces.
Tugra ZSST/2000 8118900	Wire suspension for luminaires of series Tugra. With decorative ceiling connection. With metal clamp for use of triangle.

Offer text

Multi-variable and modern tube luminaire with 75 mm profile diameter. Suitable for use in HACCP, IFS version 6 and/or BRC Global Standard Food version 7 certified companies (DIN 10500). Luminaire with limited surface temperature in accordance with DIN EN 60598-2-24, suitable for use in work locations exposed to fire hazards. For wall and ceiling mounting. Standard stainless steel mounting clips (2 pieces, V2A) with triangle included in the scope of supply. Optional accessories enable further mounting concepts. As single luminaire or for continuous line use. The continuous mounting channel of the luminaire body enables very high flexibility in positioning the fixing points. The packaging is made of recyclable cardboard, plastic-free. Multiple packaging with 28 luminaires as well as project packaging with 108 luminaires per packaging unit further reduce the general consumption of resources in the overall process. Cylindrical profile with photometrically effective prismatic structure as secondary optic. With opal profile area above and translucent profile area below the mounting channel. With symmetric narrow light distribution. With mainly direct light distribution. With slight indirect component for decorative surface illumination. Luminaire luminous flux 6400 lm, connected load 36,00 W, luminous efficiency of luminaire 177 lm/W. Light colour neutral white, correlated colour temperature (CCT) 4000 K, general colour rendering index (CRI) $R_a > 80$. Colour locus tolerance (initial MacAdam) ≤ 3 SDCM, Mean rated service life $L80(t_a 25^\circ\text{C}) = 100,000$ h. The light source is replaceable according to the ecodesign requirements (VO (EU) 2019/2020). Luminaire profile made of polycarbonate (PC). End cap colour light grey, (RAL 7035). End cap made of thermoplastically fused PC / TPE with high-quality, matt surface structure and surface finish according to VDI24. The end cap is equipped with 3 self-sealing membranes for cable cross-sections 7 mm - 13 mm as well as 3 pre-stamped feed points for PG cable glands (M20/M25) for protection rating-compliant infeed (IP66). The end cap is connected to the profile cylinder via a bayonet lock. Standard end caps included. Luminaire length 1849 mm, Luminaire height 75 mm, $\varnothing$

Luminaire body 75 mm. The gear tray is fixed to the luminaire profile with transparent devices to avoid shadowing. Permissible ambient temperature (ta) -40 °C - 45 °C. Safety class (EN 61140): I, protection rating (DIN EN 60529): IP66, impact resistance level in accordance with IEC 62262: IK10, testing temperature of wire glow test in accordance with IEC 60695-2-11: 850 °C. Weight: 3,8 kg. The connection is made by means of a plug-in terminal with mains forwarding equipment. The barrier free cable duct inside the luminaire profile facilitates the insertion of optional through-wiring or alternative uses, e.g. installing network cables. With electronic transformer, digitally dimmable (DALI). Control gear unit according to DALI-2 standard (EN 62386). Luminaire is switchable and dimmable by means of touch functionality via DALI control terminals (Touch DIM). The luminaire is suitable for operation on a 230V direct voltage supply grid (DC). The ENEC certification by an independent testing laboratory is in preparation. The luminaire complies with the fundamental requirements of applicable EU regulations and product safety legislation and bears the CE symbol.