therapy



german|engineering

EM 37 Bauchmuskel-Gürtel

Stimulation der zentralen und seitlichen Bauchmuskulatur
4 Elektroden
Einfache Anwendung
Flexibler Bauchgurt mit Klettverschluss
Universell für Bauchumfänge von 70 bis max. 140 cm verwendbar
Anschmiegsame ergonomische Form
Verschleissfreie Kontaktelektroden aus leitendem Carbonmaterial
Wasserkontakt-Elektroden (kein Kontaktgel oder Ersatzelektroden notwendig)
2 Klebeelektroden inkl. Anschlusskabel zur individuellen Stimulation als Zubehör erhältlich Art.-Nr.: 647.05
LCD Anzeige mit anschaulicher Symbolik
5 Trainingsprogramme (22-31 Minuten)
Intensität von 0 bis 40 einstellbar
Countdown-Timer mit Restlaufzeit
Trainingsspeicher-Funktion für fortlaufende Trainingskontrolle
Sicherheitsabschaltung/ Pause-Funktion/ Abschaltautomatik/ Tastensperre
Abnehmbares Bedienelement
Gurt handwaschbar
Batteriewechselanzeige
Die Anwendung ist verboten bei Trägern von Herzschrittmachern, Epileptikern, Schwangeren, Personen mit Herzrhythmusstörungen
Ausgangsspannung: max. 70V p-p bei 500 Ohm Ladung
Ausgangsstrom: max. 140 mA p-p bei 500 Ohm Ladung
Ausgangsfrequenz: 30-80 Hz
Pulsbreite: 200 µs pro Phase
Impulsform: symmetrische, zweiphasige Rechteckform
Inkl. 3 x 1,5V Batterien AAA
Produktmaße Bedienelement (LxBxH): 8,8 x 9,1 x 2,2 cm
3 Jahre Garantie
VE: 3 / Transportkarton: 6 x 3
EAN-Nr.: 4211125 64703 2
Art.-Nr.: 647.03

EM 37 Abdominal Muscle Belt

Stimulation of front and side abdominal muscles
4 electrodes
Easy to use
Flexible abdominal belt with hook and loop fastener
Flexible stomach belt for waist sizes from 28 to max. 55 in (70 to max. 140 cm)
Flexible ergonomic shape
Nonwearing contact electrodes made of conductive carbon material
Electrodes with water contact (no contact gel, no replacement)
2 adhesive electrodes incl. connecting cable for individual stimulation available as accessories Item no.: 647.05
LCD display with figurative symbols
5 training programs (22 to 31 min)
Intensity adjustable from 0 up to 40
Countdown timer with remaining time
Training memory function for continuous training control
Safety switch-off/ pause function/ automatic switch-off/ key lock
Removable control element
Belt hand washable
Battery changing indicator
The device must not be used by users of cardiac pacemakers, epileptics, pregnant woman, people with cardiac arrhythmias
Output voltage max. 70V p-p (500 Ohm load)
Output current: max. 140 mA p-p (500 Ohm load)
Output frequency: 30–80Hz
Pulse width: 200 µs per phase
Pulseform: symmetrical, dual-phase square pulses
Incl. 3 x 1.5V batteries AAA
Product measurements control element (LxWxH): 8.8 x 9.1 x 2.2 cm
3 year guarantee
Sales unit: 3 / Shipping carton: 6 x 3
EAN no.: 4211125 64703 2
Item no.: 647.03

0816 Irrtum und Änderungen vorbehalten | Subject to errors and changes

beurer