


BRUMBERG

LED recessed downlight
Artikel-Nr. 12540074









LED recessed downlight, white, round. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic / Steel, Degree of protection: according to DIN EN 60529 IP44*, Protection class: (EN 61140) I, Power: 12W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 1.200lm, Colour temperature: 4.000 K, Light colour : White, Beam angle: 100°, Adjustability: Not adjustable, With control gear: Yes, Control: on/off.

Artikel-Nr.	**12540074**
Stand:	26.10.2021 00:58

Colour temperature	4000 K
Colour	White
Beam angle	100 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic / Steel
Power	12 W
Lamp	LED
scope of delivery	inkl. Konverter zum Anschluss an 230 V-Netzspannung, schaltbar
Colour rendering	CRI > 80

Glare evaluation	UGR < 22
Control	on/off
Outer diameter	167 mm
Built-in diameter	150 mm
Installation depth	100 mm
Degree of protection	IP44*
Protection class	I
Adjustability	Not adjustable
Circuit type	Parallel conduction
Suitable for through-wiring	Yes

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.