


Recessed spot, GX5,3
Artikel-Nr. 0063.02



Recessed spot, GX5,3, chrome, round. In a compact design, for installation in tool-less rapid assembly systems. Not compatible to LED-Modules 18498002, 12823003, 12843004 and 18438002. Lamp holder: GX5.3, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V, Power: 50W, Amount of light sources / fittings: 1.0 Qty, Adjustability: Pivoted, With control gear: No, control: Dimming depending on driver.

Artikel-Nr.	0063.02
Stand:	20.07.2021 01:06

Colour	Chrome
Amount of light sources / fittings	1 Qty
control	Dimming depending on driver
Outer diameter	82 mm
Brackets	5366
Built-in diameter	68 mm
Installation depth	55 mm
Material	Aluminium
Height	3 mm
Lamp holder	GX5.3

Power	max. 50 W
Voltage	12V
Lamp	for LED-retrofill lamp
Circuit type	Parallel conduction
Degree of protection	IP20
Protection class	III
Swivel angle	25 °
Voltage type	AC/DC
Circlip	Without circlip
Adjustability	Pivoted