



LED pendant profile luminaire direct BIRO40
Artikel-Nr. 77243084



LED pendant profile luminaire direct BIRO40, black, rectangularLamp holder: LED, Mounting method: Suspended, Place of installation: Ceiling-mounted, Material: Aluminium / Acrylic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 31.4W, Luminous flux: 2.740lm, Colour temperature: 4000 K, Light colour : White, Beam angle: 80°, Adjustability: Not adjustable, With control gear: Yes.

Artikel-Nr.	77243084
Stand:	22.07.2021 02:06

control	DALI
Colour	Black
Colour of light	4000 K
Glare evaluation	UGR < 25
System efficiency	87 lm/W
Luminous flux	2,740 lm
Material cover	Satinised
Length	1144 mm
Colour rendering	CRI > 90
Beam angle	80 °

Material	Aluminium / Acrylic
Lamp holder	LED
Lamp	LED
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	I
Adjustability	Not adjustable
Width	40 mm
Height	75 mm
Circuit type	Parallel conduction
Pendulum length max.	1,500 mm