

BRUMBERG


# BIRO Circle pendant ring luminaire 600, direct

**Artikel-Nr. 13630188**






BIRO Circle pendant ring luminaire 600, direct, black, round. Suspended, Ceiling-mounted. Mounting method: Suspended, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP40, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 25W, Amount of light sources / fittings: 1.0 Qty, Light colour : White, Beam angle: 108°, With control gear: Yes. Diese Leuchte enthält eingebaute LED-Lampen. Die Lampen können in der Leuchte nicht ausgetauscht werden.

| | |
|---|---|
| **Artikel-Nr.** | **13630188** |
| **Stand:** | 18.06.2021 20:14 |

| | |
|---|---|
| Type of dimming | DALI |
| Colour | Black |
| Material cover | Plastic, opal |
| System output | 25 W |
| Colour rendering | CRI > 80 |
| Beam angle | 108 ° |
| Amount of light sources / fittings | 1 Qty |
| Outer diameter | 600 mm |
| Height | 100 mm |
| Colour rendering | CRI > 80 |

| | |
|---|---|
| Material | Aluminium / Steel / Plastic |
| Voltage | 230V AC 50Hz |
| Lamp | LED |
| Light output | Direct |
| Shipping | Incl. converter for connection to the 230-V mains voltage |
| Pendulum length max. | 5,000 mm |
| Degree of protection | IP40 |
| Protection class | I |
| Voltage type | AC |

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.