

Han 16EMC/B-HBM-DL-ML



Image is for illustration purposes only. Please refer to product description.

Part number	09 62 816 0301 ML
Specification	Han 16EMC/B-HBM-DL-ML
HARTING eCatalogue	https://b2b.harting.com/09628160301ML

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] EMC/B
Type of hood/housing	Bulkhead mounted housing

Version

Size	16 B
Locking type	Double locking lever
Field of application	Hoods/Housings for higher EMC requirements

Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Uncoated
Colour (hood/housing)	Unpainted
Material (seal)	NBR
Material (locking)	Steel, zinc plated



Pushing Performance
Since 1945

Specifications and approvals

Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes

Commercial data

Packaging size	1
Net weight	139 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140171923
eCl@ss	27440202 Shell for industrial connectors