




## LED Arbeitsplatzleuchte

### LED workplace luminaire






## UNILED SL, 1045 mm, 24V DC, Abdeckung Mikroprismen

|                               |                                     |
|-------------------------------|-------------------------------------|
| <b>Artikel-Nr.:</b>           | 110914-23                           |
| <b>EAN:</b>                   | 4260556623405                       |
| <b>Bestell-Nr.:</b>           | 110914-23                           |
| <b>Modell:</b>                | UNILED SL                           |
| <b>Bauform:</b>               | LED System- und Arbeitsplatzleuchte |
| <b>Leuchtmittel:</b>          | SMD LED                             |
| <b>Lampenleistung:</b>        | ~48 W                               |
| <b>Lampenlichtstrom:</b>      | 6417 lm                             |
| <b>Lampenlichtausbeute:</b>   | 131 lm/W                            |
| <b>Lichtverteilung:</b>       | direkt                              |
| <b>Lichtfarbe:</b>            | Tageslichtweiß (5200 - 5700K)       |
| <b>Anschlusswert Leuchte:</b> | 24V DC $\pm$ 10%                    |
| <b>Anschluss Leuchte:</b>     | M12 A-kodiert                       |
| <b>Schutzart:</b>             | IP50                                |
| <b>Schutzklasse:</b>          | III                                 |
| <b>Entblendung:</b>           | Mikroprismen                        |
| <b>Abstrahlwinkel:</b>        | 100°                                |
| <b>Betriebstemperatur:</b>    | -10... +60 °C                       |
| <b>Farbwiedergabe (Ra):</b>   | > 85                                |
| <b>Lampenlebensdauer:</b>     | > 60.000 h                          |
| <b>Material Gehäuse:</b>      | Aluminium                           |
| <b>Material Abdeckung:</b>    | Kunststoff Mikroprismen             |
| <b>Höhe [B] x Breite [C]:</b> | 35 mm x 85 mm                       |
| <b>Länge [A]:</b>             | 1045 mm / 1075 mm                   |
| <b>Gewicht:</b>               | 1600 g                              |
| <b>Bruttogewicht:</b>         | 2450 g                              |
| <b>Risikogruppe:</b>          | freie Gruppe                        |
| <b>Befestigungszubehör:</b>   | optional                            |
| <b>Dimmbar:</b>               | optional über Zubehör               |
| <b>Kennzeichnung:</b>         | CE, ETL Listed                      |
| <b>Gefertigt in:</b>          | Deutschland                         |
| <b>Besonderheit:</b>          | Hohe Lichtstreuung                  |

Lampenlebensdauer in Betriebstunden (L80/B10)

## LED Arbeitsplatzleuchte LED workplace luminaire



### UNILED SL, 1045 mm, 24V DC, micro prisms cover

|                                   |                                             |
|-----------------------------------|---------------------------------------------|
| <b>Item number:</b>               | 110914-23                                   |
| <b>EAN:</b>                       | 4260556623405                               |
| <b>Order number:</b>              | 110914-23                                   |
| <b>Model:</b>                     | UNILED SL                                   |
| <b>Type:</b>                      | LED system luminaire and workplace lighting |
| <b>Illuminant:</b>                | SMD LED                                     |
| <b>Power consumption:</b>         | ~48 W                                       |
| <b>Lamp luminous flux:</b>        | 6417 lm                                     |
| <b>Lamp luminous efficiency:</b>  | 131 lm/W                                    |
| <b>Light distribution:</b>        | direct                                      |
| <b>Light colour:</b>              | daylight white (5200 - 5700K)               |
| <b>Connected load:</b>            | 24V DC $\pm$ 10%                            |
| <b>Connection (connector):</b>    | M12 A-type encoded                          |
| <b>Degree of protection:</b>      | IP50                                        |
| <b>Class of protection:</b>       | III                                         |
| <b>Glare-free</b>                 | micro prisms                                |
| <b>Beam angle (optics):</b>       | 100°                                        |
| <b>Operating temperature:</b>     | -10... +60 °C                               |
| <b>Colour rendering (Ra):</b>     | > 85                                        |
| <b>Lamps lifetime:</b>            | > 60,000 h                                  |
| <b>Housing material:</b>          | aluminium                                   |
| <b>Cover material:</b>            | micro prisms cover                          |
| <b>Height [B] x Width [C]:</b>    | 35 mm x 85 mm                               |
| <b>Length [A]:</b>                | 1045 mm / 1075 mm                           |
| <b>Weight (net):</b>              | 1600 g                                      |
| <b>Gross weight:</b>              | 2450 g                                      |
| <b>Risk group (DIN EN 62471):</b> | free group                                  |
| <b>Mounting accessories:</b>      | optional                                    |
| <b>Dimmable:</b>                  | via optional accessory                      |
| <b>Marking:</b>                   | CE, ETL Listed                              |
| <b>Made in:</b>                   | Germany                                     |
| <b>Feature:</b>                   | high light diffusion                        |

Lamps lifetime in operation hours (L80/B10)