



**SEVEN-R LED recessed spot set, on/off switchable**

Article no. 3836 1084

Light.  
For Generations.**Tender**

LED recessed spot set, on/off switchable, Round. Toolless ceiling installation by installation springs. Ceiling cut-out Ø 68 mm, Installation depth 38 mm, Outer diameter 82 mm, Weight 0,149 kg, Reflector silver with rotationssymmetrical, deep, wide distributed light intensity. Cover plastic, transparent. Luminous flux 770 lm, Power 1 x 7 W, Light colour neutral white, Correlated color temperature (CCT) 4.000 K, Colour rendering index CRI > 80, Rated life time L70/B50 at 25 °C: 50.000 h, Housing material: Aluminium / Polycarbonate, Colour: Black, Permissible ambient temperature (ta): -20 °C - +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP20. With electronic driver, on/off switchable with integrated strain relief.

**Product Benefits**

- Round recessed spotlight made of solid aluminum with polycarbonate cover.
- Easy and tool-free mounting.
- CRI > 80.
- Low mounting depth 38 mm, diameter 82 mm, Ceiling cut-out 68 mm.
- Ceiling thickness maximum 13 mm.
- Large article variance with regard to housing color and color temperature.
- Switchable set - alternatively available in version for 350 mA and as dimmable (trailing-edge phase dimmer) set available.
- Alternatively available in square design.

**SEVEN-R LED recessed spot set, on/off switchable**

Article no. 38361084

Light.  
For Generations.

| Article data       |                                          |
|--------------------|------------------------------------------|
| Article no.        | 38361084                                 |
| GTIN               | 4251433928119                            |
| Series name        | SEVEN-R                                  |
| Short description  | LED recessed spot set, on/off switchable |
| Material           | Aluminium / Polycarbonate                |
| Colour             | Black                                    |
| Type of surface    | Matt                                     |
| Shape              | Round                                    |
| Outer diameter     | 82 mm                                    |
| Built-in diameter  | 68 mm                                    |
| Installation depth | 38 mm                                    |
| Hight              | 3 mm                                     |
| Weight             | 0.149 kg                                 |
| stamp              | MM                                       |
| Conformance        | CE, UKCA                                 |

| Lighting technology          |            |
|------------------------------|------------|
| Colour temperature           | 4.000 K    |
| Light colour                 | White      |
| Light output                 | Direct     |
| Luminous flux                | 770 lm     |
| System efficiency            | 110 lm/W   |
| Colour rendering             | CRI > 80   |
| Reflector                    | High-gloss |
| Reflector colour             | silver     |
| Beam angle                   | 38°        |
| Light sharing                | Symmetric  |
| Adjustable color temperature | No         |

| Operating technology of the luminaire |                                                                                                                                                          |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hight                                 | 3 mm                                                                                                                                                     |
| Lamp holder                           | Plug&Play                                                                                                                                                |
| Power                                 | 7 W                                                                                                                                                      |
| Voltage type                          | DC                                                                                                                                                       |
| Current                               | 350 mA                                                                                                                                                   |
| Lamp                                  | LED                                                                                                                                                      |
| Protection class                      | III                                                                                                                                                      |
| Degree of protection                  | IP20                                                                                                                                                     |
| Rated life time L70/B50 at 25 °C      | 50,000 h                                                                                                                                                 |
| Bulb change possible                  | The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person. |

**SEVEN-R LED recessed spot set, on/off switchable**

Article no. 3836 1084

Light.  
For Generations.

| Operating technology of driver |                 |
|--------------------------------|-----------------|
| Article No. of used driver     | 17662000        |
| Length                         | 68 mm           |
| Width                          | 35 mm           |
| Hight                          | 21 mm           |
| AC nominal voltage min         | 90 V            |
| AC nominal voltage max         | 264 V           |
| Frequency max                  | 60 Hz           |
| Dimmable                       | No              |
| Control                        | on/off          |
| Starting current               | 10 A (max.10ms) |
| Power min                      | 1 W             |
| Power                          | 7.2 W           |
| Output current                 | 350 mA          |
| Degree of protection           | IP20            |
| Protection class               | II              |
| Flicker-free                   | Yes             |

| Mounting technology         |                                           |
|-----------------------------|-------------------------------------------|
| Mounting method             | Recessed mounting                         |
| Place of installation       | Ceiling-mounted                           |
| Adjustability               | Pivoted                                   |
| Swivel angle                | 30°                                       |
| Max. ceiling thickness      | 13 mm                                     |
| Further references          | No cover with thermal insulation material |
| Material cover              | Plastic, transparent                      |
| Suitable for through-wiring | Yes, with optional accessories            |

| Packing data            |                                                                                                                                                                                                                                                                                                                                                                                |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Gross weight            | 0.266 kg                                                                                                                                                                                                                                                                                                                                                                       |
| Length of packaging     | 95 mm                                                                                                                                                                                                                                                                                                                                                                          |
| Packaging width         | 75 mm                                                                                                                                                                                                                                                                                                                                                                          |
| Packaging hight         | 95 mm                                                                                                                                                                                                                                                                                                                                                                          |
| Disposal at end of life | <p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p> |