LED2WORK
INTELLIGENCE IN LIGHT

LED Arbeitsplatzleuchte
LED workplace luminaire

PROFILED DC, 1200 mm, Abdeckung Mikroprismen, 24V DC

Artikel-Nr.:	150814-01
EAN:	4260556623801



Bestell-Nr.:	150814-01
Modell:	PROFILED
Bauform:	Profilleuchte mit T-Nut rückseitig
Leuchtmittel:	SMD LED
Lampenleistung:	~32 W
Lampenlichtstrom:	4410 lm
Lampenlichtausbeute:	145 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24V DC ± 10%
Anschluss Leuchte:	M12 Steckverbinder A-kodiert
Schutzart:	IP40
Schutzklasse:	III
Entblendung:	Mikroprismen
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +60 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Kunststoff
Höhe [B] x Breite [C]:	65 mm x 45 mm
Länge [A]:	1200 mm
Gewicht:	2100 g
Bruttogewicht:	2850 g
Risikogruppe:	freie Gruppe
Befestigungszubehör:	optional
Dimmbar:	optional über Zubehör
Kennzeichnung:	CE
Gefertigt in:	Deutschland
Besonderheit:	Universal- und Systemleuchte





Lampenlebensdauer in Betriebstunden (L80/B10)

2021_V2_LED2WORK_Datenblatt Arbeitsplatzleuchte Doppelzeile 14. 4. 2022, 11:28

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com | Shop.led2work.com

LED Arbeitsplatzleuchte
LED workplace luminaire

PROFILED DC, 1200 mm, micro prisms cover, 24V DC

Item number:	150814-01
EAN:	4260556623801



Order number:	150814-01
Model:	PROFILED
Type:	pofiled luminaire with t-slot backsided
Illuminant:	SMD LED
Power consumption:	~32 W
Lamp luminous flux:	4410 lm
Lamp luminous efficiency:	145 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC ± 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP40
Class of protection:	III
Glare-free	micro prisms
Beam angle (optics):	100°
Operating temperature:	-10...+60 °C
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60,000 h
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	65 mm x 45 mm
Length [A]:	1200 mm
Weight (net):	2100 g
Gross weight:	2850 g
Risk group (DIN EN 62471):	free group
Mounting accessories:	optional
Dimmable:	via optional accessory
Marking:	CE
Made in:	Germany
Feature:	universal lighting and/or system luminaire





Lamps lifetime in operation hours (L80/B10)

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com | Shop.led2work.com